

1020-00-RAB

13.4 in. Skybar™ NEMA-4 Plastic Wi-Fi Access Point Enclosure with Opaque Screw-on Cover & Right-Angle Mounting Bracket Accessory

Collection: Skybar™ | Series: 1020

Oberon's Skybar™ 1020 series compact NEMA 4 AP enclosure is designed specifically to protect APs in challenging environments such as stadiums, auditoriums, gymnasiums, industry and outdoors. This rugged polycarbonate enclosure protects the AP from weather, pressure spray, spilling liquids, dust, and impacts, and is transparent to wireless signals so APs with body integrated antennas or small detachable antennas may be protected. The enclosure is paintable, and can be used to conceal and protect APs in many challenging locations. This is the most compact NEMA 4 enclosure for most APs. Available with clear cover (-C) or with Right Angle Bracket (-RAB) for wall mounting. For under seat installations in auditoriums and public venues, Oberon recommends using the under seat mounting (-USM30) configuration with the 30° mounting bracket.

Accessories

- [39-1020-PMK](#) - Pole Mounting Kit for Oberon 13.4 in. Skybar™ NEMA-4 Plastic Wi-Fi Access Point Enclosure, with Right Angle Bracket
- [39-RJ45-BULKHEAD](#) - Bulkhead Modular Pass-Through
- [39-CORD-GRIP](#) - Cable Gland for Unterminated and Pre-Terminated Cables
- [39-BULKHD-KIT-RPTNC\(F\)](#) - Bulkhead RPTNC connector and jumper cable to mount antennas on Oberon NEMA 4 Wi-Fi AP Enclosures
- [39-BULKHD-KIT-RPSMA](#) - Bulkhead RPSMA connector and jumper cable to mount antennas on Oberon NEMA 4 Wi-Fi AP Enclosures



Features & Benefits

- Compact, rugged NEMA 4 Skybar™ shaped enclosure for installing APs in physically challenging environments
- Virtually transparent to wireless signals
- Plastic is easily drilled and machined for custom cable ingress and installation. Enclosure is paintable
- Cover attaches with four tamper resistant stainless steel screws, available with clear cover
- Available in under seat mounting (1020-USM30) and wall mounting (1020-RAB)

Technical Specifications

- Design: Compact, rugged polycarbonate AP enclosure designed for surface mounting AP indoors or outdoors, and for under seating and riser installation, wall mounting, or light pole mounting. Conceal and protect AP and cabling
- Performance: Designed to NEMA 1, 2, 4, 4X, 12, and 13, and IEC529-IP66 specifications for indoor/ outdoor wet, dirty, or corrosive environments. UV stabilized for exposure to direct sunlight. Transparent to wireless signals. Paintable
- Oberon Skybar™ shaped screw on cover with gasket. Cover screws must be torqued to 8 in-lbs. Cover screws are recessed into cover. Comes with standard and tamper resistant screws

Have questions about any of our solutions?

Contact us at **877-867-2312** or Sales@oberoninc.com

Wall Mounted



3D view for 1020-00-RAB →

Measurements (Maximum values*):

Width: 9.3 in.
 Back-box: xx in.
 Height: 11.29 in. Depth: 7.06 in.
 Item Weight: 6 lbs.
 Shipping Weight: 7 lbs.

Includes:

- (1) Enclosure
- (1) T-Bar Bracket
- (4) M4 x 20 mm Captive Phillips Lid Screws
- (4) M4 x 20 mm Captive Torx Lid Screws
- (4) #6 x 5/16 in. Pan Head Thread-Forming Screws for Plastic
- (4) #6 x 5/16 in. Flat Head Thread-Forming Screws for Plastic
- (4) Cushioning Washers
- (1) Right Angle Bracket (For -RAB SKUs Only)
- (4) M4 x 12 mm Button Head Socket Cap Screw (For -RAB SKUs Only)
- (1) 30° Angle Bracket (For -USM30 SKUs Only)
- (1) Metal Double Gang Outlet Box Flat Blank Cover (For -USM30 SKUs Only)
- (4) #8 x 5/16 in. Phillips Truss Head Screws (For -USM30 SKUs Only)
- (4) #10 x 1/2 in. Phillips Pan Head Screws (For -USM30 SKUs Only)
- (4) #10 EPDM Rubber Sealing Washers (For -USM30 SKUs Only)
- (4) #10 Stainless Steel Washers (For -USM30 SKUs Only)
- Installation Instructions

- Internal universal T-bar bracket to attach most vendor's APs
- -C configuration has a clear screw on cover to allow visibility of status LEDs
- -RAB configuration mounts AP in preferred horizontal orientation on walls. Right angle bracket acts as a sun shield to reduce solar heat load
- -USM30 mounts AP at 30° angle in under seat installations, or on high wall
- For similar enclosures accommodating Cisco Series 4800 APs, please refer to Oberon Models 1021 or 1022
- AP max. operating temperature should be de-rated by 11° C inside the enclosure, when solar loading is not present (See Oberon application note)
- For outdoor installation, the 1020 is very light grey to reduce solar loading. Painting the 1020 a darker color will increase solar loading. Avoid mounting 1020 where it is directly exposed to the sun. The -RAB and -RAB-PMK versions right angle bracket acts as a solar shield
- Construction: Gray Textured UL94-V0 Polycarbonate Enclosure Base, Gray Textured UL94-V0 Polycarbonate Enclosure Cover (For -00 SKUs Only), Clear Textured UL94-V0 Polycarbonate Enclosure Cover (For -C SKUs Only), 18 Ga. White Powder Coated Steel T-Bar Bracket, 10 Ga. Gray Powder Coated Steel Right-Angle Bracket (For -RAB SKUs Only), 0.10 in. Gray Powder Coated Aluminum 30° Angle Bracket (For -USM30 SKUs Only)
- Exterior Size: 9.30 x 13.38 x 3.96 in. (236.2 x 339.9 x 100.6 mm)
- Interior Size: 9.02 x 10.74 x 3.68 in. (229.1 x 272.8 x 93.5 mm)

Fits the following AP's:

Aruba

AP-205, AP-215, AP-225, AP-305, AP-315, AP-325, AP-505, AP-515

Cisco

1600i/1700i/2600i/2700i/3500i/3600i/3700i Series, 1830i/1850i Series, 2800i/3800i Series, 9115AXI, 9117AX, 9120AXI, 9130AXI

Extreme Networks

460i, AP305C, AP410i, AP505i / AP510i

Meraki

MR32/34/42, MR33, MR52/53

Mist

AP41, AP43

Ruckus

R550, R650

Ubiquiti

UniFi UAP-AC-HD, UniFi UAP-XG